

International Journal of Computer Science and Mobile Computing



A Monthly Journal of Computer Science and Information Technology

ISSN 2320-088X

IJCSMC, Vol. 4, Issue. 6, June 2015, pg.658 – 662

RESEARCH ARTICLE

A LPC Integrated Spectral Subtraction Model Acoustic Feedback Cancellation

Deepak Saini

Student, M.Tech (ECE), Guru Jambheshwar University of Science and Technology, Hissar
write2deepaksaini@gmail.com

Sandeep Dhull

Asstt. Prof, ECE Dept, Guru Jambheshwar University of Science and Technology, Hissar

Abstract: Speech is the most adaptive communication adaptive by human as well as computer for interaction. The speech can be captured online or from distance input source devices. But these devices have the limitation to include some kind of impurities in the signal. One such problem commonly found in such speech signal is Acoustic feedback problem. It is considered as the sharp background instrumentation noise included as the loop. The identification of this kind of noise is always a challenge for speech signal. In this present work, a hybrid model is defined for noise cancellation. The results shows that the work has improved the speech signal and provided the effective results
Keywords: Speech, Acoustic Feedback Cancellation, LPC, Spectral Subtraction, DWT

I. INTRODUCTION

Speech is the raw form of biometric signal used to provide the communication or information transition by a person. The human to computer interaction is also performed using speech. There are number of voice commanders available to provide the speech adaptive operations. Speech is also having the significance in many of the authentication systems. These authentication systems include the speech content based authentication and the speaker level authentication. Another associated application area for speech processing is the language adaptive translation. It means, the speech contents of one language can be transformed to other language. Such kind of transformation can be performed between different language forms.

But the outcome of these all applications and processes depends on the speech quality. As the speech is collected from raw source it can have number of integrated impurities. These impurities disrupt the speech signal feature so that the overall accuracy of any of speech processing is degraded. There is the requirement to remove these signal impurities and provide the effective speech communication. The speech signal enhancement is considered as the preprocessing activity

included with each speech processing application and process. The effectiveness of these applications depends on the accuracy of the speech signal enhancement methods. In this paper, a more robust and adaptive method is defined for speech signal enhancement. This paper is basically focused on the acoustic feedback cancellation over the speech signal.

A) Acoustic Feedback

The acoustic path exist between the device and speaker, it actually generally a loop so that the function level application is obtained over the signal. The block diagram of acoustic feedback loop is shown in figure 1.




Figure 1 : Block Diagram of Acoustic Feedback

The public communication system mostly infected with acoustic feedback which is also called howling. This kind of signal grows the signal unboundedly and gives the element based clipping. The howling is generally loud and disturbed form of noise. It is required to identify the acoustic feedback and remove it. The stability adaptive criteria are required to analyze the adaptive problem and resolve it.

The speech Acoustic Feedback Cancellation is the major requirement for any of the speech processing which is been resolved in this paper by defining a hybrid model. The presented work is defined as a layered approach for speech enhancement. In this section, the speech signal problems and processing applications are explored. The section also explained the concept of acoustic feedback and its effect on speech signal. In section II, the work presented by the earlier researchers is discussed. In section III, the proposed work model is presented and discussed. In section IV, the conclusion obtained from the work is presented.

II. EXISTING WORK

In this section, the work defined by earlier researchers is discussed. Most of the researchers defined work for noise reduction and speech signal enhancement. Author[1] has presented a work on speech signal improvement using vector quantization model. Author defined performance adaptive approach to identify the parametric change based on the fractional adaptation. Author defined the analysis under different statistical vector. Author presented the noise adaptive improvement to the signal so that the overall performance will be improved. Author[2] has provided an adaptive model to improve the degraded quality of speech signal. Author analyzed the signal under frequency domain and provided the adjustment to the signal so that the high quality improvements will be achieved. Author provided the improved signal communication for internet application. Author provided the improvement in the quality of signal.

Author[3] has provided a work on speech signal improvement using the adaptive filtration model. Author used the wavelet based decomposition model for frequency based signal separation and reduced the complexity of the signal. Author applied work based on five different signal improvements. Author adopted the model under the bit rate estimation with signal improvement and provided the speech enhancement so that the adaptive signal improvement is achieved. The method discussed in this work includes wavelet transformation, DWT, quantization model, thresholding, encoding etc. The signal reconstruction is here performed to provide the adaptive signal communication. Author[4] has provided a comparative model for filtration modeling and relative improvement in the parameters. The work includes the signal level enhancement so that quality signal adaptation is achieved from the work.

Author[5] has provided a work on speech signal processing for tamil datasets so that the improved signal transition and improvement will be achieved. Author provided the signal enhancement using DCT, LPC and the DWT approaches. Author provided the high quality improvement over the speech so that the improved signal communication will be achieved from the work. Author obtained the improved signal communication with derived signal value so that the

applied signal communication will be formed from the work. Author provided the adaptive signal communication so that the effectiveness of signal will be improved. Author[6] has provided a work on high quality signal processing and the signal encoding using different encoders. Author provided the improvement over the speech with relative delay specification. Author achieved the shape driven analysis over the signal with time and frequency domain and provided the codec integrated improvement so that the improved signal form will be obtained from the work. Author[7] has provided a work on signal compression modeling under the speech enhancement adaptive modeling. Author analyzed the signal under decomposition model and provided the bandwidth adaptive optimization so that the improved signal form is obtained from the work. Author provided the high level signal improvement so that the effective signal improvement can be gained from the work. Author[8] has provided the work coefficient vector adaptive communication of speech signal so that the prediction to the noise constraints can be obtained from the work. The analysis can be here done under specification of different associated noise vectors with specification of thresholding and the band adaptive modeling so that the improved signal communication will be formed from the work. Author provided the signal improvement under the variation analysis so that the change analysis will be performed and the signal will be improved. Author[9] defined a work on sub band division based capacity derivation model for speech signal improvement. Author presented the adaptive analysis model for transition of signal in actual signal form. Author[10] provided a work on the encoding method applied to analyze the error over the signal at early stage and provided the adaptive signal improvement will be done. Author[11] provided a work on signal analysis under spectral method so that the frequency based modification over the signal can be obtained

III. RESEARCH METHODOLOGY

In this present work a layered model is presented to identify the acoustic feedback problem over the speech signal and provided the adaptive improvement over the speech. The complete work is here divided in three subsequent stages. Where the outcome of one phase is taken as the input to the other. In first phase of this model the frequency signal analysis is obtained. To resolve the signal level problem, the Spectral subtraction method is applied. This method is frame adaptive analysis performs the signal level encoding to identify the high frequency noise over the speech signal. Once the problem is identified, the relative absolute value is subtracted from the speech and the improved signal form is obtained from the work.




Figure 2 : Presented Model

Here figure 2 is showing the complete descriptive model of this work along with associated problem resolution and the method applied. In first phase, where the high level acoustic identification is done using spectral subtraction method. This model is defined under the frame adaptive modeling so that the improved signal form is obtained from the work. Once the improved signal form is obtained, in second stage, the probabilistic analysis over the signal is done. In this stage, the LPC modeling is applied to improve the signal. The LPC is the predictive model applied in the window adaptive form. In final stage of this model, the DWT adaptive modeling is defined for frequency adaptive analysis. In this stage, the frequency adaptive analysis is applied over the signal so that the improved signal form will be obtained from the work. The work model has analyzed the signal adaptively and provided the complete solution in terms of noise reduction.

IV. RESULTS

The presented work is implemented in matlab environment and the analysis of the work is performed on different speech signals. These signals are collected from external web source and present in the form of .wav file. The proposed model is applied over the signal for speech signal enhancement. The analysis is here done on 5 different speech signal and the parameter taken for analysis is MSE (Mean Square Error). Lower the MSE value, more effective the signal is considered. The obtained results are discussed here




Figure 3 : MSE Analysis

Here figure shows that the maximum MSE value obtained here is .7 which shows that the work has provided the significant results for most of the signals. The analytical results of first two signal is very much improved and for other speech signals, the results are significant.

V. Conclusion

In this paper, an improved method is defined for speech signal enhancement in case of acoustic feedback problem. The presented model is applied on real time speech signals. The analysis results show that the work has improved the signal up to an extent.

REFERENCES

- [1] John H. L. Hansen, "Markov Model-Based Phoneme Class Partitioning for Improved Constrained Iterative Speech Enhancement", 1063-6676/94@1994 IEEE
- [2] Sharon Gannot, "Iterative and Sequential Kalman Filter-Based Speech Enhancement Algorithms", IEEE TRANSACTIONS ON SPEECH AND AUDIO PROCESSING 1063-6676/98@1998 IEEE
- [3] Huaiyu Dai, "A Joint Speech Coding-Enhancement Algorithm for MBE Vocoder", International Conference on Communication Technology ICCT'98
- [4] Benito Carnero, "Perceptual Speech Coding and Enhancement Using Frame-Synchronized Fast Wavelet Packet Transform Algorithms", IEEE TRANSACTIONS ON SIGNAL PROCESSING 1053-587X/99@1999 IEEE
- [5] Chin-Teng Lin, "Single-Channel Speech Enhancement in Variable Noise-Level Environment", IEEE TRANSACTIONS ON SYSTEMS, MAN, AND CYBERNETICS—PART A: SYSTEMS AND HUMANS 1083-4427/03© 2003 IEEE
- [6] *Te-Won Lee*, "SPEECH ENHANCEMENT BY PERCEPTUAL FILTER WITH SEQUENTIAL NOISE PARAMETER ESTIMATION".
- [7] Amarnag Subramanya, "SPEECH MODELING WITH MAGNITUDE-NORMALIZED COMPLEX SPECTRA AND ITS APPLICATION TO MULTISENSORY SPEECH ENHANCEMENT", ICME 2006 1424403677/06©2006 IEEE
- [8] Esfandiar Zavarehei, "Noisy Speech Enhancement Using Harmonic-Noise Model and Codebook-Based Post-Processing", IEEE TRANSACTIONS ON AUDIO, SPEECH, AND LANGUAGE PROCESSING 1558-7916© 2007 IEEE
- [9] Chang Huai YOU, "AUTOREGRESSIVE PARAMETER ESTIMATION FOR KALMAN FILTERING SPEECH ENHANCEMENT", ICASSP 2007 1424407281/07©2007 IEEE
- [10] Yu Shao, "A Generalized Time-Frequency Subtraction Method for Robust Speech Enhancement Based on Wavelet Filter Banks Modeling of Human Auditory System", IEEE TRANSACTIONS ON SYSTEMS, MAN, AND CYBERNETIC—PART B: CYBERNETICS 1083-4419© 2007 IEEE
- [11] Hari Krishna Maganti, "Speech Enhancement and Recognition in Meetings With an Audio-Visual Sensor Array", IEEE TRANSACTIONS ON AUDIO, SPEECH, AND LANGUAGE PROCESSING 1558-7916© 2007 IEEE